



ENABLING TECHNOLOGIES INC
The Supreme Braille Dot Quality!

BRAILLEPLACE

High Production

The BraillePlace Braille Embosser from Enabling Technologies is our highest volume double-sided, production embosser. It produces Braille on the traditional tractor feed Braille paper at a speed of 300 characters per second, or about 1,000 Braille pages per hour.

Accomodate to the most demanding production centres in the world, BraillePlace was designed from the ground up to be a high-production paper embosser that produces high-quality double-sided Braille.

Even though the BraillePlace is built for speed, it is surprisingly quiet because it is built into a self-contained, steel, free standing enclosure on casters. In fact your whole box of traditional Braille paper is stored inside the embosser while it is in operation, even after the braille has been embossed.

If you require high-quality Braille in a high-production environment, then the BraillePlace is the embosser for you.



CAPABILITIES AND FEATURES OF THE BRAILLEPLACE

- Embossing speed of up to 300 characters per second
- 4 Megabyte text buffer
- Comes with ET Speaks speech feedback
- Supports graphics up to 17 DPI
- Dynamic Braille Scaling for different Braille sizes
- Embosses high-quality, double-sided Braille on continuous form, tractor feed Braille paper up to 13.25 inches wide
- Embosses up to 45 Braille characters per line and up to 27 lines per page
- All modular construction, built with high-quality components
- Includes 90 day factory warranty (one-year parts warranty), USB to Parallel cable, line cord and user manual
- Dimensions: 39"W X 30"D x 58"H

PRINTING:

- Printing Speed: Double Sided/Interpoint 300* characters per second
- Line Width: 45 characters maximum
- Lines Per Page: 27 lines maximum
- Paper Width: Adjustable 1.5 inches to 13.25 inches (3.8 to 33.6 cm)
- Page Length: Selectable. 1 inch to 12 inches
- Paper: Continuous tractor feed paper
- Paper Weight: Variable (100-pound traditional Braille paper is recommended)

PHYSICAL DESCRIPTION:

- Width: 39 inches (99.1 cm)
- Depth: 30 inches (76.2 cm)
- Height: 58 inches (147.3 cm)
- Shipping Weight: 950 pounds (431.30 kg)
- Enclosure: Built in a self contained, free standing enclosure on casters

ENVIRONMENTAL:

- Temperature: Operating or Storage: 35 F to 100 F (2 C to 37.8 C)
- Humidity: Operating or Storage: 10% to 95% noncondensing

ELECTRICAL:

- Line Voltage: 220 - 240 VAC, 50/60 Hz, single-phase, 20A
- Fuse Rating: 250V, 10A slow blow (2)
- Interface: (Port 1) Centronics compatible parallel. (Port 2) Asynchronous Serial, EIA RS-232D, DTE (Port 3) ET Speaks, serial

COMPABILITY:

- All Windows Operating Systems through Windows 8

REQUIREMENTS (NOT INCLUDED):

- Windows based computer with Parallel, Serial or USB port
- Braille Translation software
- Braille Paper

* Actual printing speed may vary based on paper grade setting, page layout and data format. Specifications are subject to change.